

IPNext210™ Hybrid IP-PBX System

High-performance Next Generation Hybrid IP-PBX Solution

Web based Smart Multimedia Manager



Presence Terminal
(AP-PT100)



IPNext210

AddPac

AddPac Technology


2011, Sales and Marketing

Contents


- Login
- Main Screen
- Menu Structure
- System Information
- Network
- Service
- VoIP Interface
- System Monitoring
- User Management
- Device Management
- Call Management
- Conference Management
- User Presence Service Management
- Media Service Management
- UMS Service Management



Login




Main Screen



AddPac

www.addpac.com

Menu Structure



System Information

The screenshot shows a web-based management interface for an IP-PBX system. The left sidebar navigation includes: PBX (172.16.19.50:389), System Management (System Information, Network, Service, Voice Line, System Monitoring), Smart Directory Management, User Management, Device Management, Fault Management, Call Management, Conference Management, Presence Management, Media Management, and Unified Messaging Management.

The main content area displays the "System Information" panel, which lists various system parameters:

Name	Value
System Model	IPNEXT50_G2
Host Name	IP-PBX
System Password	*****
APOS Version	8.24
SMM Version	3.5.3119
Time Zone	
Current Time	Mon Jun 2 13:09:20 2008
Running Time	0 days 00:23:44
CPU Utilization	18%
Memory Utilization	Total: 131072 KB, Used: 111074 KB, Free: 19998 KB
WAN Interface	IP address: 172.16.19.50, Subnet mask: 255.255.0.0
LAN Interface	

Below the main panel are three smaller tables: "Service", "Voice Line", and "External Server".

- Service:** A table showing network service status (enable/disable) for various protocols like ftp, telnet, http, syslog, rtp, ddns, ldap, and dns.
- Voice Line:** A table showing port configuration (Port, Type, Status) for ports 0/0 and 0/1.
- External Server:** An empty table for displaying external server information.

The bottom status bar shows: 2008-07-16 오후 2:00:36, Version 3.5.3119, 172.16.19.50:389, administrator, and 인터넷 | 보조.

Annotations with arrows point to specific features:

- Pointing to the "Service" table: "Display status of network service (enable or disable) of IP-PBX"
- Pointing to the "Voice Line" table: "Display the VoIP interface status of IP-PBX such as Port Number, Type, idle status"
- Pointing to the "External Server" table: "Display utilization of System Storage"
- Pointing to the "System Information" table: "Show the basic information (Model, Version, Time, CPU, memory utilization, Interface, etc) of System, and Host Name, Password, Timezone, dateTIme information is changeable by entering edit mode."

Network (cont..)

The screenshot shows the Smart Multimedia Manager interface (http://172.16.19.50/smartsmm.htm) running in Internet Explorer. The left sidebar shows a tree view of PBX management features, with 'Network' selected under 'System Management'. The main 'Network' tab is active, displaying configuration for two interfaces:


- WAN (Lan0) Interface:** This section is highlighted with a blue box and a callout. It shows the IP address as 172.16.19.50, network mask as 255.255.0.0, and mode set to Static IP. A green arrow points from the 'Static IP' mode label to the 'A.B.C.D' placeholder in the Network Mask field.
- LAN (Lan1) Interface:** This section is highlighted with a yellow box and a callout. It shows the mode set to None, with IP Address and Network Mask fields both empty. A green arrow points from the 'None' mode label to the 'A.B.C.D' placeholder in the Network Mask field.

Both sections include MAC (Hardware) Address fields (0002.a4ff.ff50 and empty respectively) and MAC Address Clone fields (empty and optional respectively). The bottom status bar shows the date (2008-07-11), version (3.5.3111), IP (172.16.19.50:389), and administrator user.


WAN(LAN0) Interface Configuration : IP version4 Address, Operation Mode (Static IP, PPPoE, DHCP)

LAN(LAN1) Interface Configuration : IP version4 Address, Operation Mode (None, Bridge, IP Share, NAT, Static IP)

Network



Service




The screenshot shows the 'Service' configuration page of the Smart Multimedia Manager. The left sidebar lists various system management categories under 'PBX (172.16.19.50:389)'. The 'Service' option is selected. The main panel contains several service configuration sections:


- TELNET**: Server Port is set to 23.
- HTTP**: Server Port is set to 80. An 'Authentication' checkbox is checked.
- NTP**: Primary NTP Server and Secondary NTP Server fields are empty. Interval is set to 0.
- Dynamic DNS**: Fields for Dynamic DNS Server, Host Name, User Name, Password, and Life Time are empty.
- SNMP**: Server Port is set to 161.
- FTP**: Control Port is set to 21, and Data Port is set to 20.
- Syslog**: Log Level is set to 'debug', Log Server is set to 514, and Log Server Address and Port (default: 514) is also set to 514.
- LDAP**: Server Port is set to 389. User ID is set to 'Manager' and Password is masked.

A green callout box highlights the 'Basic Networking Service Configuration' section, which includes Telnet, SNMP, HTTP, FTP, NTP, Syslog, Dynamic DNS, and LDAP settings. The callout box text is:
Basic Networking Service Configuration
(Mode Setting and Change): Telnet, SNMP,
HTTP, FTP, NTP, Syslog, Dynamic DNS,
LDAP)


VoIP Interface (Line)




VoIP Interface (Digital Map)



VoIP Interface (Service)



System Monitoring



User Management

Smart Multimedia Manager - Windows Internet Explorer
http://172.16.19.50/smartsmm.htm

File View Search Tools Help

AddPac Smart Multimedia Manager AddPac Technology

PBX (172.16.19.50:389)

- System Management
- Smart Directory Management
- User Management
 - Administrators
 - Phone Users [4]
 - 5f [4]
- Device Management
 - Devices [3]
 - Device Pool
 - Device Profile
- Monitoring
- Fault Management
- Call Management
- Conference Management
- Presence Management
- Media Management
- Unified Messaging Management

Phone Users

Location /5f

Filter

Filter Name	Rule	Word	Advanced Search	Find	Full Search
User Name	begins with				

Name User ID Type Phone Number Description

jyeon chol	cyeon	User	1010	
kwon jh	jhkown	User	1009	
choi jinsuk	jschoi	User	1007	
lee minji	mjlee	User	1008	

Total Users : 4

2008-07-16 오후 2:10:11 Version 3.5.3119 172.16.19.50:389 administrator

완료 인터넷 | 보호 모드: 해제 100%

IP-PBX Phone User management

Device Management

The screenshot shows a Windows Internet Explorer window displaying the 'Smart Multimedia Manager' interface. The URL in the address bar is <http://172.16.19.50/smartsmm.htm>. The title bar reads 'Smart Multimedia Manager - Windows Internet Explorer'. The main content area is titled 'Devices' and displays a table of managed devices:

Device Name	Model	Status	IP Address	Device Pool	Description
upgrade	Auto Upgrad...	Static	172.16.19.50	default	
IP_PBX_19.50	IPNEXT50	In service	172.16.19.50	default	

The left sidebar shows a navigation tree under 'PBX (172.16.19.50:389)'. The 'Device Management' node is expanded, showing 'Devices [3]' and '5F [0]'. A yellow arrow points from this section to a callout box containing the text: 'Device Management for IP phones, Video Phones, Softphone, Application Server, etc'.

Call Management

Smart Multimedia Manager - Windows Internet Explorer
http://172.16.19.50/smartsmm.htm

File View Search Tools Help

AddPac Smart Multimedia Manager AddPac Technology

PBX (172.16.19.50:389)

- System Management
- Smart Directory Management
- User Management
- Device Management
- Fault Management
- Call Management
 - Configuration
 - Dial Plan
 - Partition
 - Partition Access List
 - Phone Number
 - Phone Number Digit Map
 - Routing Pattern
 - Routing Group
 - Routing List
 - Number Translation Rule
 - Translation Pattern
 - Inbound Access Rule
 - Automatic Alternate Routing(AAR) Group
 - QoS & CAC
 - Supplementary Service
 - Advanced Service
 - Monitoring
 - History
- Conference Management
- Presence Management
- Media Management
- Unified Messaging Management

Phone Number

Filter

No.	Phone Number	Partition	Pickup Group	Partition Access List	Park Group	Hunt Group	Descr
1	1000	5F					
2	1001	5F					
3	1002	5F					
4	1003	5F					
5	1004	5F					
6	1005	5F					
7	1006	5F					
8	1007	5F					
9	1008	5F					
10	1009	5F					
11	1010	5F					
12	1011	5F					
13	1012	5F					
14	1013	5F					
15	1014	5F					
16	1015	5F					
17	1016	5F					
18	1017	5F					
19	1018	5F					


Total Numbers : 101 Search Results : 101

2008-07-16 오후 2:25:37 Version 3.5.3119 172.16.19.50:389 administrator 100%


인터넷 | 보호 모드: 해제 완료

Call related Parameter Setup and Configuration (Dial Plan, QoS, CAC, Supplementary Service, Advanced Service, Monitoring, History..)


Conference Management



User Presence Service Management



Media Service Management



Unified Messaging Service Management

The screenshot shows a web-based management interface for the Smart Multimedia Manager. The title bar reads "Smart Multimedia Manager - Windows Internet Explorer" and the URL is "http://172.16.19.50/smartsimm.htm". The main window has a blue header with the "AddPac" logo and "Smart Multimedia Manager" text. On the left is a navigation tree under "PBX (172.16.19.50:389)" which includes System Management, Smart Directory Management, User Management, Device Management, Fault Management, Call Management, Conference Management, Presence Management, Media Management, Unified Messaging Management (selected), Configuration (selected), Message Box Configuration, Unified Message Box, Unassigned Address (selected), Synchronize Message Box, and Monitoring. The right side displays a table titled "Unassigned Address" with columns: No., Address Pool, Address, Partition, Path, User, and Description. The table lists 19 entries from 1 to 19, all with "default" in the Address Pool column and "1000" through "1018" in the Address column. A green callout box points to the "Unassigned Address" row in the table, containing the text: "Parameter Setup and Configuration for UMS service (Unified Messaging Box, Unassigned Address, Synchronize Message Box, Monitoring..)". The bottom status bar shows the date and time "2008-07-16 오후 3:23:12", version "Version 3.5.3119", IP "172.16.19.50:389", user "administrator", and a language setting "인터넷 | 보호 모드: 해제".

No.	Address Pool	Address	Partition	Path	User	Description
1	default	1000	5F			
2	default	1001	5F			
3	default	1002	5F			
4	default	1003	5F			
5	default	1004	5F			
6	default	1005	5F			
7	default	1006	5F			
8	default	1007	5F			
9	default	1008	5F			
10	default	1009	5F			
11	default	1010	5F			
12	default	1011	5F			
13	default	1012	5F			
14	default	1013	5F			
15	default	1014	5F			
16	default	1015	5F			
17	default	1016	5F			
18	default	1017	5F			
19	default	1018	5F			



Thank you!

AddPac Technology Co., Ltd.
Sales and Marketing

Phone +82.2.568.3848 (KOREA)
FAX +82.2.568.3847 (KOREA)
E-mail sales@addpac.com