

Hardware Specifications

Main Chassis	High Solidity ABS Chassis
CPU	High Performance RISC + DSP (Digital Signal Processor)Integrated Processor
Memory	4MB Flash Memory 32MB SDRAM Main Memory
GSM Interface	8-Port GSM Interface 8-Port Antenna Interface 8-Port SIM Card Interface
Network Interface	2-port 10/100Mbps Ethernet Interface(RJ45)
Console Port	1-Port RS232C Interface (RJ45)
Power ON/OFF Switch	
Front LED	Power LED, LAN0 LED, LAN1 LED, Analog Port LEDs

Power and Operation Management

Operation Environment	Temperature 0°C to +50°C (32° to 122°F) (operating), -40°C to +85°C (-40° to 185°F) (storage), Humidity 5% ~ 95%
Power Supply	AC110~220VAC 50/60Hz Free Voltage, 5V 5Amp. 25 Watt, Internal Power Supply
Demension	55mm x 300mm x 174mm(H x W x D)
Weight	1.86Kg

Voice over IP Service Features

Voice and Audio Codec	G.711, G.723.1, G.726, G.729, etc
VoIP Signaling Protocol	SIP/H.323 VoIP Signaling Protocol (Dual Stack) ITU-T H.323 Gateway, Gatekeeper Support SIP Proxy Server Interoperability
Echo Cancellation	G.165 and G.168 Compliant
Voice Processing	VAD, CNG, Dynamic Jitter Buffer Operation
DTMF	Detection and Generation, RFC 2833 Compliant
Telephone Features	On-screen Dial Pad, Caller ID & Hold
Voice QoS	Enhanced QoS Management for Voice Traffic

GSM Service

GSM Dialing	Two-Stage Dialing Support
GSM Module Management	PIN, IMSI, Power, (No) Shutdown Setting, Up/Down, Current Power Level Display
Black List	GSM/VoIP Inbound Call Black List
White List	GSM/VoIP Inbound Call White List
LCR (Least Cost Routing)	GSM Traffic Metering, Scheduling, Simulator
GSM SNMP	GSM Standard MIB

WAN, IP Routing and Other Features

WAN Protocol	Point-to-Point Protocol (PPPoE) for ADSL
IP Routing	IPv4 Static and IEEE 802.1Q VLAN Routing
Other Features	DHCP Server and Relay, NAT/PAT, IEEE Standard Transparent Bridging (Spanning Tree Bridging and Concurrent Routing Bridging Protocol), NTP, Cisco Style Command Line Interface (CLI), DNS Proxy, UPnP, MAC Address Filter Service DNS Proxy, Dual-MAC Address, VLAN, DNS Update Feature, STUN Service for Private IP, Tunneling Service etc.

Operation and Management Features

Network Management	Standard SNMP Agent (MIB v2) Support, Telnet, Command Line Interface via Telnet (Public, Private IP Support), Web Based Management (Network, H.323, SIP, etc) Remote Firmware (APOS) Upgrade via FTP/TFTP Support, VPMS (VoIP Plug & Play Management) System's Client Support
Operation & Management	Performance Analyzing (Process, CPU, Interface), Configuration Backup and Restore for APOS Management, Debugging and Diagnosis Features, System Booting/Rebooting through Watch-Dog, Data Logging Features, IP Traffic Statistics through Accounting Support
Security Features	IP Packet Filtering, Access List, Access Control and Data Protections, Enable/Disable for Specific Protocols Multi-level User Account Management, Auto-disconnect for Telnet/Console Sessions, PPP User Authentication Support (PAP/CHAP)

GSM, VoIP, LED, Network Interface of AP-GS808



1. CPU RUN LED
2. LAN0 LED
3. LAN1 LED
4. GSM Port LEDs
5. 10/100Mbps LAN0 Interface
6. 10/100Mbps LAN1 Interface
7. Console Port
8. GSM Port 0 Antenna
9. SIM Card Slot 0
10. GSM Port 7 Antenna
11. SIM Card Slot 7
12. Power Inlet
13. Power On/Off Switch

AddPac

www.addpac.com

AddPac Technology Co., Ltd.

2/3/5F, Kyung-An Bldg., 769-12, Yeoksam-Dong Kangnam-Gu, Seoul, 135-080, Korea
Phone: +82-2-568-3848, Fax: +82-2-568-3847, e-mail: sales@addpac.com