

---

Category	S/W Release Version	Date
SIP	v6.10	4. Mar. 2003

## SIP RFC2833 DTMF-relay

VoiceFinder AddPac VoIP gateway supports RFC2833 (RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals) using SIP protocol.

This feature is applied to AP1000, AP1005, AP2110, AP2120, AP2520, AP3100, AP3120, and AP3220 models.

### - Related Commands

Below commands are configuration commands

```
AP1100# conf
```

Enter configuration commands, one per line. End with CNTL/Z

```
AP1100(config)# dial-p v 1001
```

```
AP1100(config-dialpeer-voip-1001)# dtmf-relay ?
```

```
rtp                DTMF relay by RTP payload defined by proprietary
```

```
rtp-2833           DTMF relay by RTP payload defined by RFC 2833
```

```
h245-alphanumeric DTMF relay by H245 alphanumeric
```

```
h245-signal        DTMF relay by H245 signal
```

```
AP1100(config-dialpeer-voip-1001)# dtmf-relay rtp-2833
```

-> It is possible to relay the DTMF tone using RFC2833 rtp payload, if both voip dial-peers are set to rtp-2833.

- Default value

Dtmf relay is set disabled.