

VoIP

AP-MG3000 Next Generation Media Gateway



Technical Sales and Marketing

AddPac Technology

www.addpac.com

AP-MG3000 Next Generation Media Gateway

Media Gateway Connectivity



No.	Interface	Explanation
(1)	Asynchronous Serial	One(1) RS-232C serial ports for Local system management
(2)	AUX Port	One(1) RS-232C serial ports for AUX serial Interface such as Modem
(3)	Fast Ethernet	Two(2) 10/100 Fast Ethernet Ports for LAN interface
(4)	Module Slot 0-2	Two(2) Digital E1/T1 Interface Module Slot

AP-MG3000 Media Gateway Product Overview

APOS Internetworking Protocol Stack



AP-MG3000 Media Gateway Product Overview

APOS Internetworking S/W World

- **APOS Internetworking Software World**
  - AddPac Operating System (APOS)
  - Support Industry Standard
  - Integrated Networking Protocols
  - Optimized Performance & Functionality
  - Easy to use, Installation, and Maintenance



AP-MG3000 Media Gateway Product Overview

APOS Internetworking S/W World (cont.)



AP-MG3000 Media Gateway Product Overview

Digital E1/T1 Interface Connectivity

- **E1/T1**
  - ISDN PRI signaling support (network mode, user mode)
  - R2 signaling support (calling number receive support)
  - DTMF signaling support
  - Clock source master mode, slave mode support
  - In case of channel allocation, ascending / descending random support
  - One physical E1/T1 interface can be divided into several logical channel groups
  - Super frame, extended super frame T1 framing support
  - AMI, AMI-BELL, AMI-GTE, AMI-DDS, B8ZS T1 line code support
  - Immediate, Wink-start T1 CAS type support
  - SS7*







AP-MG3000 Media Gateway Product Overview

Voice over IP Service

- **H.323, SIP, and MGCP Triple Stack**
  - Concurrent Triple VoIP Stack Software
  - Single Hardware with Three VoIP Service
  - New APOS-NX Version
- **H.323**
  - ITU-T Standard H.323 v3 Support
  - Support H.245 Tunneling
  - Including H.235 Security Features
- **SIP**
  - IETF RFC3261 or RFC2543 SIP Standard
- **MGCP**
  - IETF RFC2705bis-02 Standard MGCP 1.0



AP-MG3000 Media Gateway Product Overview

Voice over IP Service (cont.)

- **H.323**
  - Fast connect, normal connect support
  - H.245 tunneling support
  - Q.931 response message setting for inbound VoIP calls
  - H.245 logical channel open timing selection function
  - Start H.245 procedure support
  - DTMF / Hook flash relay with H.245 alphanumeric / signal
  - Secondary gatekeeper support
  - Gatekeeper assignment according to the domain name
  - Gatekeeper discovery with multicast
  - Lightweight RRQ support
  - Signaling TCP port assignment
  - Resource threshold setting with RAI
  - H.235 clear-token, crypto-token support
  - canMapAlias support
  - Technical prefix (supported prefix) support
  - Public IP assignment in NAT environment

- **SIP**
  - Gateway-based / Endpoint-based registration support
  - Secondary proxy-server assignment function
  - SIP signaling port change function
  - SIP proxy server assignment according to the domain name
  - T.38 real-time fax relay support
  - DTMF relay support with RFC2833 / OPTION message
  - Re-INVITE support
- **MGCP**
  - Secondary call agent assignment function
  - Default package assignment
  - Announcement Server Package, Generic Media Package, Handset Package, Line Package, Trunk Package support
  - MGCP call agent assignment according to the domain name
  - T.38 real-time fax relay support
  - DTMF relay support based on RFC2833

AP-MG3000 Media Gateway Product Overview

Voice over IP Service (cont.)

- **Voice Codec**
  - G.711 A-Law, G.711 U-Law
  - G.726 r16, G.726 r32
  - G.729A
  - G.723.1 r63, G.723.1 r53
  - VAD (Voice Activity Detection) function support
  - DTMF relay support (H.323, SIP, MGCP common) based on RFC2833
- **RTP**
  - Redundant RTP packet transmission in case of severe packet loss
  - Dynamic jitter buffer management and RPT packet jitter and loss compensation with heuristic & DSP error concealment
  - Static jitter buffer setting support
  - Voice frame per RTP packet number control for each codec
  - In-band ring-back tone support
  - Virtual ring-back tone support
  - Tone parameter change support

- **FAX**
  - Fax relay mode supporting T.38, inband-T.38, bypass mode
  - Lost packet compensation with redundant setting in case of T.38 fax relay
  - Fax relay mode, rate setting for remote end



AP-MG3000 Media Gateway Product Overview

VoIP Call Managements

- **VoIP Call Controls**
  - Hot line connection function with PLAR (Private Line Auto Ring Down)
  - Leased line emulation function
  - Connection monitoring function
  - Fault tolerant with Redundancy and Call Distribution among Gateways for load balancing
  - Call attempt with IP address
  - H.323, SIP, MGCP inbound call connection for each voice port
  - Multiple E.164 setting for one voice port
  - One E.164 or digit pattern can be assigned to more than one voice port
  - Hunting with Longest match/ priority/ sequence/ random
  - One stage call setup by Digit forwarding
  - Call barring with specific digit patterns
  - Calling and called number conversion for PSTN outbound calls
  - PSTN rerouting in case of VoIP call attempt failure

- **VoIP Call Controls (cont.)**
  - Call transfer for internal calls
  - Call pickup for internal calls
  - Calling and called number conversion for VoIP outbound calls
  - Calling and called number conversion for VoIP inbound calls
  - Fax broadcasting call control



AP-MG3000 Media Gateway Product Overview

Enhances QoS Managements

- **Enhances Transmit Voice QoS Features**
  - Voice Traffic Priority Queuing
  - QoS Service Profiling
  - Providing Virtual Network Transmit Algorithm
  - Real-time Voice Traffic QoS Support
  - RTP Packet Transmit Interval Control
  - Supporting RTP Packet Redundancy Scheme
  - IP Header Control such as ToS, Diffserv

- **Enhances Receive Voice QoS Features**
  - Dynamic Jitter Buffer Management
  - Error Concealment
  - Support T.38 FAX Data Error Recovery Scheme



AP-MG3000 Media Gateway Product Overview

IP and WAN Protocols

- **IP Routing Protocols**
  - Multi-protocol Internetworking Services
  - Static IP routing
  - RIP v1/v2 (opt.)
  - OSPF v2 routing protocols support (opt.)
  - Transparent Bridging (IEEE Spanning Tree Protocol)
- **WAN Protocols**
  - Point-to-Point over Ethernet Protocol (PPPoE)



AP-MG3000 Media Gateway Product Overview

Network Managements

- **SNMP**
  - Standard Simple Network Management Protocol(SNMP) Agent support
  - MIB v1 and v2 Support
- **Web-based Management**
  - Standard Digital E1/T1 Voice Interface
- **Watch-dog Function**
  - Hardware, Software watch-dog services
- **Remote Management**
  - Telnet
  - Rlogin
  - Console
- **Auto Upgrade Service**
  - HTTP server based APOS image and configuration file auto-upgrade support
- **Batch Job Function**
  - Text based script downloading



AP-MG3000 Media Gateway Product Overview

Security Managements

- IP packet filtering
- IP access list
- User authentication function
  - Password Authentication Protocol (PAP)
  - Challenge Handshake Authentication Protocol (CHAP)
- Enable/Disable specific protocols
- Auto-square connect of console and Telnet session
- Account Management function for multi-level user
- SNMP/TELNET/FTP/HTTP/TFTP port assignment function
- SNMP/TELNET/FTP access list management
- Boot mode security checking function



AP-MG3000 Media Gateway Product Overview

Network Scalability

- Bridging Service
  - Spanning Tree Bridging protocol (IEEE) support
- DHCP
  - Server and Relay
- IP Accounting
- PAT (Port Address Translation)
- NAT (Network Address Translation)
- Cisco Style CLI (Command Line Interface)
- PPTP (Point-to-Point Tunneling Protocol)
- NTP (Network Time Protocol)
- FTP/TFTP
  - Server and Client support
- DNS
  - Dynamic DNS Client support



AP-MG3000 Next Generation Media Gateway

AP-MG3000 Hardware Specification



AP-MG3000 Next Generation Media Gateway

AP-MG3000 Hardware Specification



AP-MG3000 Next Generation Media Gateway

AP-MG3000 Network Module



AP-2LAN Module

2-Port 10/100Mbps Fast Ethernet Interface

2-Port Asynchronous Serial Interface

AP-MG3000 Media Gateway Product Overview

AP-MG3000 Digital Voice Module



MG3000-E1 Module



MG3000-E2 Module



MG3000-E4 Module



MG3000-T1 Module



MG3000-T2 Module



MG3000-T4 Module

AP-MG3000 Media Gateway Product Overview

AP-MG3000 Hardware Specification

AP-MG3000 Hardware Specification			
MG3000 Main Board	Processor	64bit High-End Microprocessor	
	Memory	Flash Memory	16Mbyte
		SDRAM	128Mbyte High Speed SDRAM
		Boot Memory	512Kbyte Flash Memory
	Network Interface	Two(2) 10/100M Fast Ethernet Ports	
		1-Port RS-232C Interface for Local System Management(1 x RJ45)	
		1-Port RS-232C AUX Port for Modem Interface (1 x RJ45)	
Number of Slot		One(1) Network Module and Two(2) Digital Voice Module Slots	
Digital Voice Module		APV2-E1,T1 : One(1) Port Digital E1,T1 Interface Module	
		APV2-E2,T2 : Two(2) Port Digital E1,T1Interface Module	
		APV2-E4,T4 : Four(4) Port Digital E1,T1 Interface Module	
Power Input		VAC 110~220V Free Voltage, 50/60Hz, 25Watt	
Operating Temperature		0°C ~ 50°C	
Storage Temperature		-40°C ~ 85°C	
Width x Depth x Height		43 x 435 x 205(mm) - 19" Rack Mountable Chassis	
Weight		4.8kg	

AP-MG3000 Voice Networking Configuration

VoIP Gateway Appl. (Inter-office calls)



Voice Call Flow

PSTN Interface

Voice+Data, Ethernet or WAN Interface

TRUNK n x E1 Voice Interface for PSTN Interworking

Leased Line/ATM/Frame-Relay/IP Router, xDSL/Cable Modem, etc.

AddPac AP-MG3000 Media Gateway

Analog Phone

AP-MG3000 Networking Configuration

VoIP Gateway Appl.(VoIP to PSTN Inter-working Call Flow)



FXS Analog Voice Interface

Voice Call Flow

Voice+Data, Ethernet or WAN Interface

TRUNK n x E1 Voice Interface for PSTN Interworking

Leased Line/ATM/Frame-Relay/IP Router, xDSL/Cable Modem, etc.

AddPac AP-MG3000 Media Gateway

Analog Phone

AP-MG3000 Media Gateway Product Overview

AP-MG3000 Ordering and Pricing

- **AP-MG3000 Media Gateway**

  AP-MG5000-01 : AP-MG3000 Standard Configuration
  - Two(2) Gigabit Ethernet Interface
  - One(1) RJ45 Console Port
  - One(1) RJ45 Asynchronous RS-232C Port
  - 64bit RISC CPU, 8MB Flash, 64MB SDRAM
  - APOS v5.xx with Operation Manual
  - Including CAB-LAN, CAB-CON



MG3000-E1 : 1 Port Digital E1 Interface Module
MG3000-T1 : 1 Port Digital T1 Interface Module
MG3000-2E1 : 2 Port Digital E1 Interface Module
MG3000-2T1 : 2 Port Digital T1 Interface Module
MG3000-4E1 : 4 Port Digital E1 Interface Module
MG3000-4T1 : 4 Port Digital T1 Interface Module
CAB-LAN :RJ45 Ethernet Cable
CAB-CON :RJ45 RS-232C Console Cable

AP-MG3000 Media Gateway Product Overview

AP-MG3000 Comparison Table

	AP-MG3000 Media Gateway
▶ Digital Voice Interface Modules	Up to 2
▶ Asynchronous Port	1
▶ 10/100 Mbps Ethernet Ports	2
▶ Console Port	1
▶ Main CPU	High-End Power PC 64Bit RISC
▶ Main Flash Memory	8Mbyte
▶ Main Memory	64Mbyte
▶ Internetworking OS	APOS
▶ H.323, SIP, MGCP VoIP Protocol, T38 FAX	YES
▶ PPPoE, PPTP Network Protocols	YES
▶ Enhanced QoS Management Feature	YES
▶ IP Routing Protocols Including NAT	YES

Thank you !

www.addpac.com